

# MADA FIBER JOINT TAPE

## Technical Data Sheet

TDS-ACC-R46-Rev2 Fiber Joint Tape - 2024



### Product Description

Mada Fiber Joint Tape is composed of twisted strands of fiber glass woven at right angles to one another for reinforcing drywall joints. Mada Fiber Joint Tape is easy to apply, eliminates the need for embedding coat, fuses with the compound for stronger joints, eradicates bedding coat and provides smooth finished joint.

### Field of Application

Mada Fiber Joint Tape is self adhering fiber mesh tape for use with setting type joint compounds.

### Manufacturing Standards

In compliance with ASTM C475 and ASTM C 840.

### Product Characteristics

Parameters	Details
Width (mm)	50
Length (m)	90
Mesh Size (mm)	2.85x2.85
Mass (g/m <sup>2</sup> )	65
Tensile Strength (N/50mm)	400
Packing	24Rolls/Cartoon

### Handling and Storage

- All materials should be delivered in their original, unopened packages and stored off the ground in an enclosed shelter and protected from weather. Damaged or deteriorated materials should be removed.
- Good housekeeping and regular safe removal of waste materials are recommended. Avoid contact with eyes, skin and clothing. Minimize generation of dust.
- Fiberglass Mesh Tape should not be stacked more than two pallets in height.
- Store in a cool, dry ventilated area away from sources of heat, moisture and incompatibilities.
- This product has no known adverse effect on ecology.

### Installation Guidelines

- Position the Mada fiber tape and spread jointing compound along each joint.
- To minimize the risk of cracking, ensure jointing compound is pushed through the fiber tape well into any gaps between the plasterboards / cement board.
- The products should not be used for purposes other than those shown on the Mada Technical Proposal.